

75004515

Benchtop model	Yes	230V
[-] FULL SPECIFICATIONS		
Max. Speed	15200rpm	
Capacity	3L (4 x 750)	
Refrigerated	Yes	
Max. RCF	25314 x G	
Hertz	50Hz	
Voltage	230V	
Temperature Range (Metric)	-10° to +40°C	
Control	Microprocessor	
Display	Digital	
Height (English) Exterior	14.2 in.	
Height (English) Open Cover	34.5 in.	
Height (Metric) Exterior	36cm	
Height (Metric) Open Cover	90cm	
Length (English) Exterior	26.4 in.	
Length (Metric) Exterior	67kg	
Memory	99 programs (5 with direct access key)	
Motor Type	Direct, brushless induction, low-profile	
Net Weight (English)	255.7 lb.	
Net Weight (Metric)	116kg	
Timer	99 hrs., 59 min. plus HOLD	
Width (English) Exterior	29.3 in.	
Width (Metric) Exterior	74.5cm	
Item Description	X3R (Refrigerated), 230V 50Hz	
Certifications/Compliance	IVD compliant; IEC 61010-1, IEC 61010-2-020, IEC 61010-2-101; 230V models meet EN 292, EN 61326, EN 55011B. UL, CE, CSA, Certified Biosafety	
Type	Benchtop model	